



WL350 Firewall®

Excellent purifying performance,
easy operation and stylish design



Purified water for the workplace

With a choice of hot and cold water, the WL350 Firewall is the preferred solution for any small or medium size workplace looking for great tasting water, reliability and guaranteed quality.

Advanced technology

The WL350 features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall purification

Waterlogic's patented Firewall technology utilizes a highly effective UV purification system to purify the water to 99.9999% bacteria free and acts as a final barrier to pathogens right at the point of dispense.



BioCote® protection

The key surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

Certified purity for peace of mind

The Firewall technology has been tested and certified by the WQA to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – no other water cooler features these standards of certification for microbiological water treatment systems together. This means that Firewall technology delivers the safest water possible for the workplace.

Features

Firewall UV technology purifies the water at the point of dispense and sanitizes the faucet with every use

Energy saving sleep mode to significantly reduce power consumption when unit is not in use

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Water options



cold



sparkling

ambient



hot

extra hot

Number of users

up to 30

Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems

NSF P231
Protocol for
Microbiological Purifiers



CE QUALITY & SAFETY
GUARANTEED

*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

13.6"/345mm (W) x 40.2"/1022mm (H) x 14.4"/367mm (D)

Countertop:

13.6"/345mm (W) x 17.7"/450.5mm (H) x 14.4"/367mm (D)

Dispensing area height

8.5" (215mm)

Weight

Countertop: 42lbs (19kg)

Freestanding: 58lbs (26kg)

Standard filtration supplied

Freestanding: Carbon Block (CBC) with lead, cyst and asbestos reduction, Granular Activated Carbon (GAC)

Countertop: Carbon Block (CBC) with lead, cyst and asbestos reduction

Storage capacity

Hot tank: 1.6 liters

Cold tank (Freestanding): 4 liters

Cold tank (Countertop): 2 liters

Compressor

Compressor 120V/60Hz

Water temperatures settings

Cold: 41°F/ 5°C

Hot: 187°F/ 85°C



Call us today

Waterlogic Commercial Products, LLC

Tel: 800-288-1891

11710 Stonegate Circle
Omaha, NE 68164

www.waterlogicusa.com
customerservice@waterlogicusa.com

For more information, visit www.waterlogic.com